

SONY Colour Body Camera

FEATURES

- Colour Camera with SONY 1/3" EXview HAD CCD sensor in metal Case.
- Digital Signal Processor (DSP) chip-set for image control.
- High Sensitivity, low smear, high anti-blooming, and high S/N ratio.
- Powerful functions: (AES), (AI), (AGC), (AWB) and (BLC).
- Supports both Video Drive & DC Drives lens.
- Supports C & CS Mount Lens
- Built-in anti-aliasing and IR-cut optical filter



Ez-259

380 TVL

0.03 Lux



C/CSMount

SPECIFICATION

| Model | Ez-259 |
|----------------------------|---|
| Image Pick-up Device | SONY 1/3" EX-View HAD CCD |
| Effective Picture Elements | NTSC: 510*492, PAL: 500*582(H*V) |
| Horizontal Resolution | 380 TVL |
| Minimum Illumination | 0.03 LUX @ F1.2 |
| Auto Electronic Shutter | AES ON: NTSC: 1/60s~1/100,000s, PAL 1/50s~1/110,000s OFF: NTSC: 1/60s, PAL 1/50s |
| Auto Iris Control | Video-Drive Lens & DC-Drive Lens both supported |
| Gamma Characteristics | 0.45 |
| Lens Mount | C & CS mount adjustable |
| Gain Control | Automatically |
| White Balance | Automatically (2500K~9500K) |
| Back Light Compensation | ON/OFF Switch |
| Synchronous System | Negative sync. Internal |
| Video Output | 1 Vp-p Composite Video / 75 Ohms. BNC connector. |
| Power Supply | DC 12V / AC110V / AC230V 3.5W |
| Operating Temperature | -10C to 50C (14F to 120F) |
| Audio (Optional) | 2Vp-p 50 Ohms. RCA connector. |

*Specification and image are subject to change without any notification