



EZ-DVR-7204

Standalone DVR



Key Features

- User-friendly GUI for easy operation
- Up to 1024×768 VGA output resolution
- Simultaneous VGA and CVBS output
- Scheduled and event recording parameters configurable per camera
- Partial digital zoom by using mouse when in PTZ control mode
- Different recording storage period configurable for each channel
- NTP, SADP, DHCP protocols supported



	EZ-DVR-7204
Video & Audio compression	H.264 & G.711 Audio Compression
Analog video input	4-ch, BNC connector (1.0 Vp-p, 75 Ω); PAL / NTSC adaptive
Audio input	4-ch, RCA connector (2 Vp-p, 1 kΩ)
Voice talk input	1-ch, RCA (2.0 Vp-p, 1 kΩ)
VGA output	1-ch, resolution: 1024 × 768 / 60 Hz
CVBS output	2-ch, BNC connector (1.0 Vp-p, 75 Ω); Resolution: PAL: 704 × 576, NTSC: 704 × 480
Audio output	1-ch, RCA connector (Linear, 1 kΩ)
Recording resolution	4CIF / 2CIF / CIF / QCIF
Frame rate	4CIF / 2CIF: 12fps, CIF / QCIF: 25fps (P) / 30fps (N)
Video bit rate	32 kbps ~ 2048 kbps, or user-defined (Max. 3072 kbps)
Stream type	Video/ Video & Audio
Audio bit rate	64 kbps
Dual stream	Support
Synchronous playback	4-ch
Type	1 SATA interface
Capacity	Up to 2TB capacity for each interface
Network interface	1, RJ45 10 M / 100 M adaptive Ethernet interface
Serial interface	1 RS-485 interface, 1 RS-232 interface
USB interface	2, USB 2.0
Alarm input /output	4 Inputs, 1 Outputs
Power supply	12 VDC
Consumption	≤10 W (without hard disk or DVD-R/W)
Working temperature & Humidity	-10°C ~ +55°C & 10% ~ 90% Humidity
Dimensions (mm) & Weight	315(W) × 230(D) × 45(H) & ≤2.5kg (without hard disk or DVD-R/W)