



EZ-DVR-7304/7308/7316

Standalone DVR



Key Features

- H.264 video compression
- UP to 4CIF recording
- Each channel supports dual stream
- Up to 16-ch synchronous playback
- Up to 4 SATA HDD at 2TB each



	EZ-DVR-7304	EZ-DVR-7308	EZ-DVR-7316
Video compression	H.264		
Audio Compression	OggVorbis		
Analog video input	4-ch,	8-ch,	16-ch,
Audio input	4-ch, RCA(2.0Vp-p, 1kΩ)		
Voice talk input	1-ch, (Using AUDIO IN 1)		
VGA output	1, Resolution: 1024×768/60Hz		
Preview Resolution	PAL: 704×576 NTSC: 704×480		
Audio output	1-ch, RCA(Linear electrical level, 600Ω)		
Recording resolution	4CIF/DCIF/2CIF/CIF/QCIF	4CIF/2CIF/CIF/QCIF	
Frame rate	4CIF/DCIF: 8fps 2CIF: 16fps CIF: 25(P)/30(N)fps	4CIF: 8fps 2CIF: 16fps CIF: 25(P)/30(N)fps	4CIF: 6fps 2CIF: 12fps CIF: 25(P)/30(N)fps
Video bit rate	32Kbps~1024Kbps, or user-defined		
Audio bit rate	16kbps		
Synchronous playback	4-ch	8-ch	16-ch
Type	4 SATA interface		
Capacity	Up to 2TB capacity for each interface		
Network interface	1, RJ45 10 M / 100 M adaptive Ethernet interface		
Serial interface	1 RS-232 interface; 1 RS-485 interface, 1 RS485 Keyboard interface		
USB interface	2, USB 2.0		
Alarm input /output	16 Inputs, 4 Outputs		
Power supply	100~240VAC, 6.3A, 50~60Hz		
Consumption	≤40 W (without hard disk or DVD-R/W)		
Working temp & Humidity	-10°C ~ +55°C & 10% ~ 90% Humidity		
Dimensions (mm) & Weight	440(W) × 390(D) × 70(H) & ≤8000g		