

### 26X Zoom 480TVL External PTZ Camera with True Day/Night ICR



The EZ-PTZ-26X offers exceptional picture quality in both day and night environments. With 26X optical and 12X digital zoom this high quality speed dome is ideal for professional CCTV installations.



### Features

- 1/4" SONY EX-VIEW HAD CCD
- 26X ZOOM, f=3.5 (WIDE) TO 91MM (TELE)
- TRUE DAY/NIGHT (ICR)
- CONTINUOUS 360° PAN ROTATION RANGE
- MANUAL PAN SPEED OF 0.4° - 320°/S
- 128 PRESETS
- 12X DIGITAL ZOOM (312 x TOTAL)
- ADJUSTABLE SLOW SHUTTER
- 7 ALARM INPUTS, 2 ALARM OUTPUTS
- AUTO FLIP
- PRIVACY MASKING
- IP 66 WEATHERPROOFING



# EZ-PTZ-26X

## 26x External True Day/Night PTZ Camera



### Dimensions



### Optional Brackets

(Pole mount adaptor, wall mount and corner mount adaptor)



### Optional PTZ-26x-Keyboard



### Specification

Model	EZ-PTZ-26X
CCD Type	1/4" Sony Ex-View CCD
Pixel Array	PAL 752 (H) x 582 (V)
Horizontal Resolution	480 TVL
Minimum Illumination	1.0 Lux (typical) (F1.6, 50 IRE)
Manual Pan Speed	0.4° - 320°/S
White Balance	Auto, ATW, Indoor, Outdoor, One-Push, Manual
Tilt Rotation Range	Tilt 90°, with auto-flip
IP Rating	IP66
Electronic Shutter	1/1 – 1/10'000 sec, 22 steps
Focal Length	26X zoom, f=3.5 (wide) to 91mm (tele) F1.6 to F3.8
Power Source	AC24 ±4V 1.5A
Power Consumption	12W Indoor, 50W Outdoor
Operating Temperature	0° to 50° C (Indoor) -40° to 60° (Outdoor)
Weight	400g (approx)
Dimension	300mm x 231mm