

GML-E800V

Model Name

GML-E800V

Features

- * Indoor/Outdoor Operation
- * Sony 1/3" EXview HAD CCD
- * Digital Signal Process
- * Horizontal Resolution of 540TVL
- * Automatic White Balance(AWB)
- * Material : Aluminum
- * IP66
- * DC12V (Non-polarity)
- * CE, FCC, RoHS Compliance



Specifications

General

Signal System	PAL
Image Device	Sony 1/3" EXview HAD CCD
Total Pixel	470K
Effective Pixel	(H)752x(V)582
Lens	Vari-Focal Fixed IRIS Lens (4~9mm-STD, 2.6~6mm, 9~22mm-OPT)
Resolution	540TVL
Minimum Illumination	0.05 Lux
Scanning System	625 Lines 2:1 Interlace
Scanning Frequency	(H)15.625KHz(V)50Hz
Sync. System	Internal
S/N Ratio	More Than 48dB (AGC Off)
Video Output Signal	VBS 1.0Vp-p Composite, 75ohm
Electronic Shutter	1/50~100,000

Function

White Balance	Automatic White Balance (AWB)
Gamma	0.45

Electrical

Power Source	DC12V (Non-polarity)
Power Consumption	180mA
Connector Video Output	BNC Cable
Power Input	Wired Type

Environmental

Operating Temperature	14°F ~ 122°F (- 10°C ~ 50°C)
Storage Temperature	-22°F ~ 140°F (- 30°C ~ 60°C)
Operating Humidity	Up to 90% RH

Mechanical

Material	Aluminum
Color	Ivory
Dimension (mm)	155(W) X 59(H)
Weight	271g

ezCCTV.com

3 City Business Park, Letchworth Garden City, Herts, SG6 1FH
 Sales: 0808 180 18 18, Technical Support: 08706 094 507, Tel: 01462 708 820
 sales@ezCCTV.com support@ezCCTV.com