

## GV-R1352 Card Reader



The GV-R1352 is a card reader designed to recognize identification cards. Featured with the Wiegand and RS-485 outputs, the unit can be connected to any standard access control panel. GV-R1352 comes with a weather sealed and IP66 compliant housing for outdoor use.

### KEY FEATURES

- Card reader with weather-proof and IP66-compliant housing
- Wiegand interface supported
- RS-485 output: 9,600 bps, connect up to 8 GV-R1352 units
- 13.56 MHz for ISO14443A (Mifare DESFire, Mifare Plus and Mifare Class)

### SPECIFICATIONS

CPU	8 bit microprocessor
Frequency	13.56 MHz for ISO14443A (Mifare DESFire, Mifare Plus and Mifare Class)
Wiegand Interface	Wiegand 26 / 34 bit, distance 30 m / 98.43 ft
RS-485	9,600 bps, connect up to 8 GV-R1352 units
Power	DC 7.5V~12V
LED	Red, Green and Blue LED
Beeper	Buzzer
Color	Black
Operating Temperature	-20 °C ~ 60 °C / -4 °F ~ 140 °F
Operating Humidity	10 ~ 90% RH (non-condensing)
Dimensions (W x H x D)	65.80 x 115.6 x 20.5 mm / 4.6 x 2.6 x 0.8 in
Weight	120 g / 0.26 lb
Certification	IP66, CE, FCC, RoHS

### The number of GV-R1352 supported by GV-AS Controllers

GV-AS Controller Model	GV-R1352 Interface	
	Wiegand	RS-485
GV-AS100	1	1
GV-AS110 / GV-AS120	1	Not support
GV-AS100 / GV-AS110 / GV-AS120 with GV-ASBOX	2	4
GV-AS100 / GV-AS110 / GV-AS120 with GV-ASNet	Not Support	2
GV-AS400	8	8