

## PRH-5480

### FEATURES

- IR LED 80M housing and cable managed bracket 24Vac
- Radiant distance up to 100m
- Cable managed housing and bracket
- Built-in auto activate heater & blower
- IP 66 Rated aluminum housing
- Adopts new enhanced power IR LED with 20,000 average operation hours
- Aluminum PCB for better heat dissipation
- Special layout of different angle LED to optimize radiant coverage
- Adjustable IR LED activation level to meet various applications
- Revolutionary enhanced power LED with output of 0.5W



PRH-5480

### SPECIFICATION

<b>Model</b>	PRH-5480
<b>Power Input Voltage</b>	AC 24V (-+10%)
<b>Radiant Distance</b>	80-100m
<b>Window</b>	110 Heat resistant glass
<b>Glass Thickness</b>	3mm
<b>Infrared LED: Wave Length</b>	850nm
<b>Angle</b>	30 Degrees
<b>Quantity</b>	17 Units
<b>Power On</b>	CDS Auto Control, Adjustable Control Point
<b>Blower Control</b>	On: 35 Degrees, Off: 25 Degrees
<b>Heater Control</b>	On: 15 Degrees, Off: 25 Degrees
<b>Suitable Camera and Lens</b>	Max. 200mm lens
<b>IP Rating</b>	IP66
<b>Mounting</b>	Bottom
<b>Construction</b>	Aluminum
<b>Power Consumption</b>	22W
<b>Operating Temperature</b>	-20 Degrees C - +60 Degrees C
<b>Dimensions</b>	Housing: 134 x 318mm (L) Bracket: 205mm (L)
<b>Weight</b>	3500g

\*Specification and image are subject to change without any notification